





- Changeover circuit with rating 5A
- Snap action contacts mechanism with long life coil spring
- Rock wipe and self-cleaning contact action
- Variety of actuators and contact arrangements
- Quick connect (faston), solder and PCB terminals
- Dimensions in accordance with DIN 41635 form B
- UL recognized component (File E212007)




Rating

5A em 250Vac


Circuitry (IEC 60947-5-1)



Form A (SPST-NO)



Form B (SPST-NC)




Form C (SPDT)

Specifications


Contact Resistance	50 mΩ maximum initial (at 1A 5Vdc)
Ambient Temperature	+85°C maximum
Degree of Protection	IP40 (EN 60529)
Operating Speed	0,5 mm/s minimum to 1 m/s maximum (at Plunger)
Mechanical Life Expectancy	10.000.000 cycles
Electrical Life Expectancy	50.000 cycles (at 5A 250Vac)
Materials	Enclosure: Thermoplastic Polyamide
	Plunger: Thermoplastic Polyamide
	Actuators: Lever: Stainless Steel (types E, R and U) Nickel Plated Brass (types D, G and J)
	Roller: Thermoplastic Polyamide
	Terminals: Brass
Contacts: Silver Alloy	

Dimensions



Dimensions in mm



Standard model - Pin Plunger actuator
with Solder Terminal



Quick Connect 0.110"
(Faston 2,8 X 0,5)
Terminal





PCB Terminal

Switch with 3 terminals.
Standard contact configuration:
11 = Common (COM)
12 = Normally Closed (NC)
14 = Normally Open (NO)


Fixation

Dimensions in mm




Integral Actuators


Dimensions in mm




Hinge Lever (Type E)




Roller Hinge Lever (Type R)




Roller Simulated Hinge Lever
(Type U)



Hinge Lever (Type G)



Roller Hinge Lever (Type J)






Roller Simulated Hinge Lever
(Type D)




















Subject to change without prior notice




Ordering Information

M M 1 G 3 N S

Application	
Plunger Force	Code
100 gr	= MM2
200 gr	= MM1 ①

Terminals		
Type	Form	Code
Solder		= S ①
Quick Connect		= F
PCB		= I

Actuator		
Type		Code
Pin Plunger		= A ①
Short Hinge Lever		= E1 ①
Hinge Lever		= E3
Roller Short Hinge Lever		= R1 ①
Roller Hinge Lever		= R3
Simulated Roller Short Hinge Lever		= U1
Simulated Roller Hinge Lever		= U3
Short Hinge Lever		= G1
		= G2
Hinge Lever		= G3
		= G4
Roller Short Hinge Lever		= J1
		= J2
Roller Hinge Lever		= J3
		= J4
Simulated Roller Short Hinge Lever		= D1
		= D2
Simulated Roller Hinge Lever		= D3
		= D4

Contact Configuration		
NO + NC		= N ①
only NO (Normally Open)		= N1
only NC (Normally Closed)		= N2

Note:

The codes market with ① are standards versions.
The other (not marked) upon request.

Special Applications

Even though the products presented in this catalog are models of regular commercial use, we are able to develop "personalized" models for special applications. Contact us. Examples:

- Enclosure UL94 V-0
- Other lengths, material and forms for the actuators.

Subject to change without prior notice






















MM Series

Subminiature Switch

Characteristics

Terminology: OF ... Operating Force
 OP ... Operating Position
 PT ... Pretravel
 DT ... Differential Travel
 OT ... Overtravel
 L Actuator Length

Actuador	OF (gf)		OP (mm)	PT max. (mm)	DT max. (mm)	OT min. (mm)	L (mm)
	MM1	MM2					
A 	200	125	8.4 ± 0.4	0.8	0.15	0.4	-
E1 	57	34	8.9 ± 1.5	2.8	0.5	0.8	5.2 ± 0.4
E3 	37	23	8.9 ± 2.3	4.4	0.8	1.3	14.4 ± 0.4
R1 	55	34	14.4 ± 1.6	2.9	0.5	0.8	5.4 ± 0.6
R3 	39	24	14.4 ± 2.2	4.1	0.8	1.2	12.6 ± 0.6
U1 	52	33	11.9 ± 1.7	3.1	0.6	0.9	6.4 ± 0.6
U3 	38	24	11.9 ± 2.3	4.2	0.8	1.2	13.6 ± 0.6
G1 	53	33	8.9 ± 1.6	3.0	0.6	0.6	7.2 ± 0.5
G2 	21	13	8.9 ± 2.0	7.6	1.4	0.1	10.4 ± 0.5
G3 	39	24	8.9 ± 2.2	4.1	0.8	0.8	14.4 ± 0.5
G4 	15	10	8.9 ± 2.7	10.4	1.9	0.15	17.6 ± 0.5
J1 	58	36	14.4 ± 1.6	2.8	0.5	0.6	5.4 ± 0.6
J2 	23	14	14.4 ± 1.9	6.9	1.3	0.1	8.6 ± 0.6
J3 	42	26	14.4 ± 2.1	3.8	0.7	0.8	12.6 ± 0.6
J4 	16	10	14.4 ± 2.6	9.7	1.8	0.1	15.8 ± 0.6
D1 	55	34	11.9 ± 1.6	2.9	0.5	0.6	6.4 ± 0.6
D2 	22	14	11.9 ± 2.0	7.3	1.4	0.1	9.6 ± 0.6
D3 	40	25	11.9 ± 2.1	4.0	0.8	0.8	13.6 ± 0.6
D4 	16	10	11.9 ± 2.7	10.1	1.9	0.1	16.8 ± 0.6

Subject to change without prior notice



KAP COMPONENTES ELÉTRICOS Ltda.